




Product Specifications | Autel EV Charger AC Wallbox

	Model	Home Version	Commercial Version
Output	Output power	7 kW / 11 kW / 22 kW	22 kW
	Output voltage	AC 230 V \pm 15%, single phase, 50 Hz AC 400 V \pm 15%, 50 Hz	AC 230 V \pm 15%, single phase, 50Hz AC 400V \pm 15%, 50Hz
	Output current	6-32 A	6-32 A
Input	Input rating	C 230 V, single phase L, N, PE, 50Hz AC 400 V, 3P+N+PE, 50 Hz	AC 230 V, single phase L, N, PE, 50 Hz AC 400 V, 3P+N+PE, 50 Hz
User interface	User interface Communication	LED + APP	LED + APP + LCD (Option)
	Authorization ChargingProtocol	WIFI, BlueTooth, RFID Autostart / APP / RFID NA	WIFI, BlueTooth, 4G, RFID Autostart / RFID / APP OCPP1.6J / 2.0J Optional
	Charge connector	IEC 62196-2 Type 1 or Type 2 plug, 5m IEC 62196-2 Type 2 Socket	IEC 62196-2 Type 1 or Type 2 plug, 5m IEC 62196-2 Type 2 Socket or Socket with shutter
Safety	RCD	AC 30 mA DC 6 mA	AC 30 mA DC 6 mA
	Electrical protection	Over current protection, Residual current protection, Short circuit, Ground (PE) protection, Over/under voltage protection, Over/under frequency protection, Over/under temperature protection, Surge protection	
	Operating temp	-40°C to 55°C (-40 F to +131 F)	-40°C to 55°C (-40 F to +131 F)
	Storage temp	-40°C to 85°C (-40 F to +185 F)	-40°C to 85°C (-40 F to +185 F)
	Operating humidity	<95% Non-condensing	<95% Non-condensing
	Altitude	<2000 m	<2000 m
	MTBF	>100.000 h	>100.000 h
Basic specifications	Dimension (WxDxH)	335 x 187 x 85 mm	335 x 187 x 85 mm
	Weight	5 kg	5 kg
	Metering	Meter IC	Certified Meter (MID)
	Protection	IP65; IK08	IP65; IK08
	Warranty	3 years	3 years
	Certified	CE EMC Class B	CE EMC Class B
	Compliance	IEC 61851-1, IEC 61851-21-2, CE EMCEU/2014/30, CE Low voltage EU / 2014/35, RED EU / 2014/53	

 **+43 664 52 52 872**
 service@autel-oesterreich.com
 www.autel-oesterreich.com