




Product Specifications | Autel EV Charger DC High Power

| | | |
|-----------------------------|-----------------------|--|
| Output | Output power | 240 kW / 360 kW |
| | Output voltage | DC150-1000 V |
| | Output current | 5-800 A (max. output of single connector: 200 A) |
| | Ripple factor | ≤ 0.5% |
| Input | Input rating | AC 400V ± 15% 3P+N+PE, 50Hz |
| | Power factor | ≥ 0.99 |
| | THD | ≤ ± 5% |
| User interface | User interface | 7 inch LCD |
| | Communication | 4G, WIFI, LAN |
| | Authorization | APP/RFID |
| | Charging protocol | OCPP 1.6J |
| | Charge connector | CCS2*4 or CCS2*2 + ChadeMo*2w |
| Safety | Electrical protection | Circuit discharge function, Insulation monitoring device (IMD), Battery reverse connection protection. Short circuit protection, Over/under voltage protection, Voltage/current limitation protection, Overheat protection, SPD, Plug temperature, monitoring function, Circuit contactor adhesion protection. |
| Environment | Operating temp | - 30°C to 50°C (-22 F to +122 F) |
| | Storage temp | - 40°C to 85°C (-40 F to +185 F) |
| | Operating humidity | < 95% Non-condensing |
| | Altitude | < 2000 m |
| | Noise | ≤ 65 dB |
| | MTBF | > 8760 h |
| Basic specifications | Dimension (W D H) | 1750*1000*1900 mm (main cabinet) 420*250*1220 mm (charger) |
| | Weight | 1400 kg ± 10 kg (main cabinet), 35kg ± 3kg (charger) |
| | Efficiency | ≥ 95% |
| | Metering | NA |
| | Protection | IP54; IK10 |
| | Warranty | 1 year |
| | Certified | CE EMC Class A |
| | Compliance | DIN 70121; ISO 15118; EN 61851-1-2001 / EN 61851-21-2001 / EN 61851-22-2001 |

 **+43 664 52 52 872**
 service@autel-oesterreich.com
 www.autel-oesterreich.com