


# Product Specifications | Autel EV Charger DC Wallbox

<b>Output</b>	Output power	30 kW
	Output voltage	DC150-1000 V
	Output current	2-66 A
	Ripple factor	≤±0.5%
<b>Input</b>	Input rating	AC 400V ± 15% 3P+N+PE, 50Hz
	Power factor	≥ 0.99
	THD	≤ 5%
<b>User interface</b>	User interface	7 inch LCD
	Communication	3G/4G, LAN
	Authorization	APP/RFID
	Charging protocol	OCPP 1.6J
	Charge connector	CCS2*1 orChadeMo*1
<b>Safety</b>	Electrical protection	Over current Protection, Short circuit, Ground (PE) protection, Over/under voltage protection, Over temperature protection, Surge protection
<b>Environment</b>	Operating temp	- 25°C to 45°C (-13 F to +113 F)
	Storage temp	- 40°C to 85°C (-40 F to +185 F)
	Operating humidity	< 95% Non-condensing
	Altitude	< 2000 m
	Noise	≤ 65 dB
	MTBF	> 8760 h
<b>Basic specifications</b>	Dimension (WxDxH)	200 x 600 x 500 mm
	Weight	26 kg
	Efficiency	≥ 95%
	Metering	NA
	Protection	IP54; IK10
	Warranty	1 year
	Certified	CE EMC Class A
	Compliance	DIN 70121; ISO 15118; EN 61851-1-2001 / EN 61851-21-2001 / EN 61851-22-2001

 **+43 664 52 52 872**  
 [service@autel-oesterreich.com](mailto:service@autel-oesterreich.com)  
 [www.autel-oesterreich.com](http://www.autel-oesterreich.com)